

SLICOAT Products



PISTONCLAD™

(coefficient of friction after break-in <0.1)

Anti Friction Coating

PISTONCLAD is a specially formulated anti friction coating used on piston skirts for gasoline, diesel and other piston powered engines.

PISTONCLAD is an excellent oil attracting coating that helps eliminate galling and fretting on mating surfaces of aluminum and steel.

PISTONCLAD has excellent high temperature stability, chemical breakdown resistant to fuels, acids and bases, brake fluids, moisture and lubricating oils

Jet Hot SLICOAT PISTONCLAD Benefits

Temp Range: to 715 ° F

Color: Black

(0.0007 -- 0.00078" applied thicknesses)

- Prevents cold start piston seizures
- Friction reduction reduces temperatures
- Quiets piston noise or rattle
- Increases piston and cylinder bore life
- Increased fuel efficiency
- Smoother running engine, Increased power
- Jet Hot Custom coating application
- Race Proven

LIMITED WARRANTY – SLICOAT® Coatings- Jet Hot believes that the above is an accurate description of the typical characteristics and or uses of Jet Hot SDF product, recommended for general use for product satisfaction. Jet Hot's sole warranty is that the product or products will meet Jet Hot's coating applications standard for high quality, free from defects for applied material, however Jet Hot SDF coatings are subject to sacrificial wear depending on intensity and duration of use.

JET HOT SPECIFICALLY DISCLAIMS ANY OTHER EXPRESSOR IMPLIED WARRANTY, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND OF FITNESS FOR USE. Your exclusive remedy and JET HOT's sole liability for breach of warranty is limited to refund of the purchase price or replacement of any product shown to be other than as warranted, and JET HOT expressly disclaims any liability for consequential damages.